

T-230 Parts Washer Compound



T-230 is specifically formulated to deal with the special requirements of cleaning brass or multiple ferrous and non-ferrous alloys in one cleaning operation. It is designed specifically to be used in spray application parts washers and ultra-sonic tanks. Not only is it capable of dispersing large amounts of particulate and solids, but also splitting oil out of solution, thus greatly extending cleaning solution life. Special sequestering agents help prevent scale build up in machines.

USAGE AND DILUTION INSTRUCTIONS

For use in spray washer applications use 4 to 8 ounces per gallon of water. Solution operating temperature should be maintained between 120° and 170° F. to maintain optimum cleaning and foaming characteristics. Exceeding 140deg. F. may discolor sensitive brass alloys.

PHYSICAL PROPERTIES

Appearance	Clear Colorless
Liquid	
Specific Gravity	1.05
pH @ 1 % Solution	10
Solubility in Water	Excellent
Odor	Mild
Flash Point	None
Stability	Stable
Foaming Action	Controlled
Metal Safety	Aluminum, Steel, Brass, Copper, Zinc

HANDLING AND STORAGE INSTRUCTIONS

This is a non-combustible alkaline liquid. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and rubber boots as necessary to avoid personal contact with this product. In case of contact, flush eyes and/or skin with plenty of water for at least 15 minutes. Consult physician and remove contaminated clothing promptly. Store product in tightly closed containers between 50° and 85° F. Rotate stock. When stored as stated above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 60 years experience. Our company has been certified to ISO 9001:2000 Quality Standards.

Refer to our Material Safety Data Sheet for additional information

Rev. 1/09



3015 Dormax S.W. Grandville, MI 49418
Phone (616-534-6103 Fax: 534-0920
www.progresschemical.com