

1502 Compound



1502 Compound is an acidic product formulated to descale copper and brass and remove solder, flux, and oxidation. It is designed to use in soak tanks or ultrasonic cleaning systems.

PHYSICAL PROPERTIES

Appearance	Clear Liquid
pH @ 1% solution	2.0
Odor	Mild
Foaming Action	Controlled
Solubility in Water	Complete
Rinsing Action	Excellent
Metal Safety	Copper & Brass
Flash Point	None
Stability	Stable
Specific Gravity	1.07

Refer to our Material Safety Data Sheet for additional information.

USAGE AND DILUTION RECOMMENDATIONS

For descaling copper and brass and removing solder, flux and oxidation from metal parts in soak tanks or ultrasonic cleaning applications, use 5 - 7 ounces per gallon of water. Solution temperature should not exceed 140° -160° F.

HANDLING AND STORAGE

This product does not pose any fire hazards. Use good industrial hygiene practices such as wearing rubber gloves and an impermeable apron to protect skin. Chemical safety goggles and face shield should be worn to protect face and eyes. If eye contact occurs, flush with plenty of water for at least 15 minutes and consult a physician. In case of skin contact, flush with copious amounts of water, removing contaminated clothing and shoes. Keep product containers tightly closed when not in use. Store in the original container between 45° and 85F. When stored as above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 65 years experience. Our quality management system has been certified to ISO 9001 Quality Standards.