

1737 Parts Washer Compound



1737 is an impingement cleaner specially formulated for ultra-high pressure spray application parts washers. This product may be used on all ferrous and nonferrous metals.

Notable product features include:

- Improves cleaning efficiency by maximizing spray force
- Excellent dispersion properties
- Excellent rinsing properties, helps prevent water spots.
- Oils removed from the parts are easily split and skimmed from the solution
- Interim process corrosion inhibitor for ferrous metals.
- Neutral pH.
- Non-hazardous, biodegradable

PHYSICAL PROPERTIES

Appearance	Green Liquid
pH @ 1% solution	9.7
Odor	Mild
Foaming Action	None
Solubility in Water	Complete
Rinsing Action	Excellent
Metal Safety	All Metals
Flash Point	None
Specific Gravity	1.062
Stability	Stable
Standard Container	55 Gallon Drum

USAGE AND DILUTION RECOMMENDATIONS

Use a minimum of 4-8 ounces 1737 compound per gallon of water. Solution temperature should be maintained between 150° and 180F. It is recommended that pump pressure settings remain between 100 and 8,000 psi.

HANDLING AND STORAGE

This product does not pose any no fire hazards. Use good industrial hygiene practices such as wearing rubber gloves and an impermeable apron to protect sensitive skin. Chemical safety goggles should be worn to protect eyes. If eye contact occurs, flush with plenty of water for at least 15 minutes and consults a physician. In case of skin contact, wash with soap and water, re-moving contaminated clothing and shoes. Store product in tightly closed containers between 50° and 85° F. Rotate stock. When stored as stated above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 65 years experience. Our quality management system has been certified to ISO 9001 Quality Standards.

Refer to our Safety Data Sheet for Additional information.