

## 660 Spray Wash Compound



Our 660 Spray Wash Compound is a heavy duty aluminum cleaner. It was formulated to remove oily soils from aluminum and ferrous metals using spray application parts washers. This low foaming cleaner was originally developed to clean aluminum castings in the automotive rebuilding industry. It is often recommended where heavily soils are present and/or both steel and aluminum parts are cleaned in the same machine.

- Efficiently penetrates a wide range of oily soils
- Excellent dispersion properties prevent redeposition
- •Especially well suited where aluminum and steel are cleaned in same machine.
- Gives maximum solution life,
- Low foaming

## PHYSICAL PROPERTIES

Appearance White Free Flowing Powder

pH @ 1% solution 10
Odor Mild
Foaming Action Very Low
Solubility in Water Excellent

Metal Safety Ferrous & Aluminum

Standard Container 400 lb Drum

## USAGE AND DILUTION RECOMMENDATIONS

Use 4 to 8 ounces per gallon of water. Maintain solution temperatures of 120° to 160° F. Higher temperatures may darken or pit aluminum. Periodic adds of 1 to 2 ounces per gallon may be made to extend cleaning solution life and maintain low foaming characteristics.

## HANDLING AND STORAGE

This is a highly alkaline product containing Sodium Hydroxide. Use good industrial hygiene practices such as wearing chemical safety goggles, rubber gloves, impermeable apron, and other appropriate protective clothing to prevent personal contact. Wash thoroughly after handling this product. In case of skin or eye contact, flush with plenty of water for at least 15 minutes and call a physician. Stock should be rotated and stored in a tightly closed container within a cool dry place to reduce caking. When stored as stated above, shelf life is a minimum of 2 years.

Progress Chemical guarantees its products will perform to your satisfaction when used in accordance to our recommendations. We back this guarantee with over 65 years experience. Our quality management system has been certified to ISO 9001 Quality Standards.

Refer to our Safety Data Sheet for Additional information.